

SOFTWARE PRODUCT DESCRIPTION

CHARON-AXP/4100 for Linux 64 bit

Product version 4.6

Document: 60-15-059-002



DESCRIPTION

CHARON-AXP/4100 is a member of the CHARON cross-platform hardware virtualization product family. CHARON-AXP creates the virtual replica of the original AlphaServer hardware inside a standard 64bit x86 compatible computer system. It will run the original Alpha binary code, including operating systems like OpenVMS and Tru64 UNIX, their layered products, and applications.

CHARON-AXP/4100 for Linux 64bit is designed to replace the AlphaServer 400, 800, 1000, 1000A, 1200, 2000, 2100, 4000, and 4100 computer systems by its virtual equivalent running on a Linux host platform.

Most of the original AlphaServer hardware is virtualized, allowing the **OpenVMS** or **Tru64** operating system and all software that is running in that environment to remain working as always. Very few changes are required to the original software (operating system, layered products, or applications). The Tru64 kernel might require a rebuild.

NETWORK

CHARON-AXP virtualizes the 10/100 Mbps Ethernet controllers from the DEC 21x4x and Intel 82558 families, ensuring support of any AlphaServer installation. Any protocol that ran over a physical Ethernet link (DECnet, TCP/IP, and LAT) will run over a virtualized link. The virtual network adapter is recognized by the operating system which assumes it will run at 10/100Mbps, but since it's virtualized it may exceed that speed when connected to a 1/10Gbps adapter in the host system. However the network performance also depends on design limitations of the guest VMS/Tru64 OS.

STORAGE

CHARON-AXP provides support for AlphaServer storage devices: disk, tape and CD/DVD drives via virtual KZPBA SCSI adapter. CHARON-AXP allows connecting Alpha SCSI devices to logical disks or tapes which appear as container files in the host operating system; as well as connecting to physical SCSI devices.

PASS THROUGH

Emulex FC adapters compatible with original AlphaServer hardware (FC KGPSA) could be used by CHARON-AXP to provide direct access to SAN.

HOSTING SERVER HARDWARE RECOMMENDATIONS

HP Proliant 3x0 G9 with Intel Haswell (Xeon E5 v3 series CPUs, at least 3.2GHz frequency) are recommended. For 1 or 2 emulated AXP CPUs, desktop Intel Core i7 4xxx CPUs are recommended. However CHARON runs on any Intel / AMD powered host with sufficient hardware resources. For every emulated AXP CPU, CHARON must have exclusive access to at least 2 CPU cores on the host server.

PERFORMANCE

CHARON-AXP running Tru64 5.1B delivers (per CPU) 388 SPEC2000 INT and 371 SPEC2000 FP on an Intel Core i7 965 (3.2 GHz) host system. CHARON-AXP benefits from the newer, faster hardware, offering owners of most AlphaServer systems equal or better performance. The constant improvements Stromasys makes to CHARON products, together with rapidly developing faster hardware, will further shift the balance to favor cross-platform virtualization.

As a reference, the following table shows performance measurements of the original AlphaServer hardware using the standard SPEC2000 benchmark.

Those numbers are available online from official SPEC2000 web page.

Single CPU benchmark	SPEC2000 INT	SPEC2000 FP
AlphaServer 4100 5/533	176	176
AlphaServer DS10 6/500	300	383
AlphaServer DS20 6/677	425	455
AlphaServer ES40 6/500	299	382
AlphaServer GS80 6/731	352	405
AlphaServer GS160 68/1000	561	581

PRODUCT LICENSE KEY

CHARON supports a range of licensing options, including local and network HASP keys, and software license keys. License preserves customer specific license parameters, allowing remote electronic updates and enabling rapid change of host systems as the CHARON executable can be installed on multiple systems.

COMMERCIAL LICENSING

The CHARON-AXP/4100 base license includes 1 virtual Alpha CPU for AlphaServer 400; 800, 1000, 1000A, 1200, 2000, and 4000; and 2 virtual Alpha CPUs for AlphaServer 2100 and 4100. An additional CPU option can be purchased separately. The amount of emulated RAM is set to the maximum supported by the AlphaServer model.

CHARON-AXP licensing allows combining multiple instances of CHARON-AXP of different Alpha models on a single multi-core host system.

CHARON DISTRIBUTION

CHARON Installation kits, Release notes, User manuals, Software Product Descriptions, and Patches are available for download through partner or direct customer login from Stromasys ftp.

CHARON UTILITIES

- **mkdskcmd** creates empty AXP disk images. Also used to transfer disk images of one type to a disk image of another type.
- **mtd** is used to create a CHARON tape image from a physical tape and to write a tape image to a physical tape.
- **ncu** manages CHARON physical and virtual network connections.
- **hasp_srm_view** displays content of CHARON-AXP license. Also used to transfer licenses from one host to another host.
- **CHARON Linux toolkit** simplifies CHARON operational management (start/stop/upgrade tasks) as well as license update and monitoring tasks.

USER ENVIRONMENT

After installation the system will behave like the AXP it replaces and should be treated like that AXP. Operating procedures will be the same and we advise not to treat it as a Linux system, despite the fact it runs on a Linux kernel. The Linux kernel can be disconnected from the network after installation.



stromasys
engineered solutions

VIRTUALIZED HARDWARE

Emulated hardware model	AlphaServer 400	AlphaServer 800	AlphaServer 1000/1000A	AlphaServer 1200	AlphaServer 2000	AlphaServer 2100	AlphaServer 4000	AlphaServer 4100
Alpha CPUs (base/maximum)	1/1	1/1	1/1	1/2	1/2	1 or 2 / 4	1/2	1 or 2 / 4
Emulated RAM	Up to 1GB	Up to 8 GB	Up to 1 GB	Up to 32 GB	Up to 2 GB	Up to 2 GB	Up to 32 GB	Up to 32 GB
Available virtual PCI slots	3	4	3/7	6	3	3	16	8
Storage adapter support	Emulated PCI SCSI KZPBA adapters (1 preloaded); up to 120 storage units (disks, tapes, and CD/DVD) supported simultaneously							
Disk storage support	Virtual disk images on a local and remote Linux file system (.vdisk container files); physical SCSI disks (/dev/sdN) and partitions (/dev/sdNL); iSCSI disks; SAN attached storage volumes							
Tape storage support	Virtual tape images on a local and remote Linux file system (.vtape container files); physical SCSI tape drives (/dev/sgN devices)							
CDROM/Floppy disk support	Virtual CD/DVDs images a local and remote Linux file system (.iso container files); physical CD/DVD drives (/dev/cdrom, /dev/srN devices) / -							
Ethernet Network support	Emulated PCI DEC 21x4x adapter family: DE435, DE450, DE500AA, DE500BA (1 preloaded DEC TULIP 21040 controller for models AS2000 and AS2100); Emulated Intel 82558 adapter family DE602							
Fiber Channel/FDDI support	Direct connection to SAN with physical KGPSA or compatible EMULEX HBA adapters							
Console/Serial lines	OPA0 console attached to a Linux terminal, a physical serial port(/dev/ttySN device), or a TCP/IP socket							
Supported operating systems	OpenVMS 6.2-1H3 – OpenVMS 8.4, Digital UNIX 3.2 – 4.0E; Tru64 UNIX 4.0F – 5.1B (also known as: Compaq or HP Tru64 UNIX)							

Host system requirements

Host operating system	Red Hat Enterprise 6.5 and 7 (with some restrictions) 64-bit and Fedora 20 64-bit on top of a physical host or on VMware ESXi 4.1 update 1 or ESXi 5.x
Host CPU/RAM	Amount of host system CPU cores $\geq 2 * (\text{amount of emulated AXP CPU cores})$; Host RAM $\geq 2 \text{ GB} + (\text{amount of emulated AXP RAM})$
Recommended Hardware	HP Proliant 3x0 G9 servers with Intel Xeon E5 v3 CPU family, frequency at least 3.2 GHz; or desktop Intel Core i7 4xxx

Ordering information

Unlimited license	CHAXP-806IP-LI
Annual license	CHAXP-806IY-LI
Annual GOLD Support	CHAXP-806IU-LI
Annual PLATINUM Support	CHAXP-806IT-LI
Backup license	CHAXP-806IK-LI
Additional CPU	CHAXP-CPUIP-LI

«Copyright © 2014 Stromasys Inc. All rights reserved. CHARON name / logo is a trademark of Stromasys SA» - zastratecrea.com

STROMASYS SA

Headquarter
Avenue Louis-Casai 84
5th Floor
1216 Cointrin
Switzerland
Phone: +41 22 794 1070
Fax: +41 22 794 1073
info@stromasys.com

STROMASYS INC

Americas Region
2840 Plaza Place,
Ste 450
Raleigh, NC 27612
United States of America
Phone: +1 919 239 8450
Fax: +1 919 239 8451
us.sales@stromasys.com

STROMASYS EMEA

Europe, Middle East & Africa
Avenue Louis-Casai 84
5th Floor
1216 Cointrin
Switzerland
Phone: +41 22 794 1070
Fax: +41 22 794 1073
emea.sales@stromasys.com

STROMASYS ASIA PACIFIC LTD

Asia Pacific Region
28/F, Room D, Tower B, Billion Centre
1 Wang Kwong Road
Kowloon Bay
Hong Kong
Phone: +852 2853 1600
Fax: +852 2853 1699
apac.sales@stromasys.com

