

# SOFTWARE PRODUCT DESCRIPTION

## CHARON-AXP/DS/ES/GS for Windows 64 bit

Product version 4.6

Document: 60-15-058-002



### DESCRIPTION

CHARON-AXP/DS/ES/GS are members of the CHARON cross-platform hardware virtualization product family. CHARON-AXP creates the virtual replica of the original Alpha Hardware inside a standard 64 bit x86 compatible computer system. It will run the original Alpha binary code, including operating systems OpenVMS and Tru64 UNIX, the layered products, and applications.

CHARON-AXP/DS/ES/GS for Windows 64 bit are designed to replace the following AlphaServer computer systems by its virtual equivalent running on a Windows host platform:

CHARON-AXP product	Hardware to replace
CHARON-AXP/DS10	AlphaServer DS10, DS15
CHARON-AXP/DS20	AlphaServer DS20, DS25
CHARON-AXP/ES40	AlphaServer ES40, ES45, ES47
CHARON-AXP/GS80	AlphaServer GS80, GS60, ES80
CHARON-AXP/GS160	AlphaServer GS140, GS160
CHARON-AXP/GS320	AlphaServer GS320, GS1280

### NETWORK

CHARON-AXP virtualizes the 10/100 Mbps Ethernet controllers from DEC 21x4x family, ensuring support of any AlphaServer installation. Any protocol that ran over a physical Ethernet link (DECnet, TCP/IP, and LAT) will run over a virtualized link. The virtual network adapter is recognized by the operating system which assumes it will run at 10/100Mbps, but since it's virtualized it may exceed that speed when connected to a 1/10Gbps adapter in the host system. The measured network performance also depends on design limitations of the guest VMS/Tru64 OS.

### STORAGE

CHARON-AXP provides support for Alpha storage devices: disk, tape, and CD/DVD drives via virtual KZPBA SCSI and virtual KGPSA FC adapters. CHARON-AXP allows connecting SCSI devices to logical disks or tapes which appear as container files in the host operating system; as well as connected physical SCSI devices.

### PASS THROUGH

FDDI DEPPFA adapter and Emulex FC adapters compatible with original AlphaServer hardware (FC KGPSA) could be used by CHARON-AXP to provide direct access to FDDI network and SAN.

### HOSTING SERVER HARDWARE RECOMMENDATIONS

HP Proliant G7 with Intel Xeon 5600 series and G8 servers with E5 and E7 CPUs, at least 3GHz frequency are recommended, however CHARON runs on any Intel / AMD powered host with sufficient hardware resources. For every emulated AXP CPU, CHARON must have exclusive access to at least 2 CPU cores on the host server.

### PERFORMANCES

CHARON-AXP running Tru64 5.1B delivers (per CPU) 403 SPEC2000 INT and 379 SPEC2000 FP on an Intel Core i7 965 (3.2 GHz) host system. CHARON-AXP benefits from the newer, faster hardware, offering owners of most Alpha systems equal or better performance. The constant improvements Stromasys makes to the CHARON products, together with rapidly developing faster hardware, will further shift the balance in favor of cross-platform virtualization.

### PRODUCT LICENSE KEY

The CHARON USB HASP license key must be permanently connected to the host system. It preserves the customer specific license parameters, allows remote electronic updates and enables rapid change of host systems as the CHARON executable itself can be installed on multiple systems.

### LICENSING

The CHARON-AXP/DS/ES/GS base license includes half of the maximum virtual Alpha CPUs. Additional CPU options can be purchased separately. Amount of emulated RAM is set to maximum supported by model.

CHARON-AXP licensing allows combining multiple instances of CHARON-VAX and CHARON-AXP on a single multi-core host system.

### DISTRIBUTION KITS

CHARON Installation kits, Release notes, User manuals, Software Product Descriptions, Patches. Available for download through partner's login on Stromasys web site

### CHARON UTILITIES

- **HASP\_View:** for viewing CHARON license content
- **HASPRUS:** for updating CHARON license
- **Network Control Center:** to manage CHARON network drivers and settings
- **DEVcheck:** provides configuration assistance for directly connected SCSI devices
- **MKdisk:** create empty AXP disk images
- **MTD:** transfer the data between physical tape and CHARON tape container file
- **CHARON Launcher:** start/stop/configure CHARON, setup CHARON services
- **Service Manager:** manage CHARON instances as services
- **HOSTprint:** redirect virtual parallel port (LPV11) to a Windows local or network printer (applicable to QBUS based CHARON systems only).
- **IDLE VMS utility:** suspend host CPU utilization if VMS is idle – energy save mode.

### USER ENVIRONMENT

After installation the system will behave like the AXP it replaces and should be treated like that AXP. Operating procedures will be the same and we advise not to treat it as a Windows system, despite the fact it runs on a Windows kernel. The product documentation includes an advisory for switching off unused Windows services and the Windows kernel can be disconnected from the network after installation.



stromasys  
engineered solutions

## VIRTUALIZED HARDWARE

Emulated AlphaServer model	DS10, DS15	DS20, DS25	ES40, ES45	GS80	GS160	GS320
Alpha CPUs (base/maximum)	1/1	1/2	2/4	4/8	8/16	16/32
Emulated RAM	Up to 32 GB	Up to 32 GB	Up to 32 GB	Up to 64 GB	Up to 128 GB	Up to 256 GB
Available virtual PCI slots	4	6	10	27	27	27
Storage adapter support	Emulated PCI SCSI KZPBA adapters (2 preloaded for DS20, DS25; 1 preloaded for GS series); Emulated PCI FC KGPSA adapters; up to 120 storage units (disks, tapes, and CD/DVD) supported simultaneously; Emulated Acer Labs 1543C IDE/ATAPI controller (1 preloaded; only virtual IDE CD/DVD devices)					
Disk storage support	Virtual disk images on a local and remote Windows file system (.vdisk container files); physical SCSI disks and partitions; iSCSI disks; SAN attached storage volumes (\\PhysicalDriveX devices)					
Tape storage support	Virtual tape images on a local and remote Windows file system (.vtape container files); physical SCSI tape drives (\\TapeX or \\SCSI devices)					
CDROM/Floppy disk support	Virtual CD/DVDs images (.iso container files); physical CD/DVD drives (\\CdRomX devices) / Physical floppy drive 1.44 MB (\\A: device)					
Ethernet Network support	Emulated PCI DEC 21x4x adapter family: DE435, DE450, DE500AA, DE500BA (2 DEC 21143 controllers preloaded for DS10, DS15, 1 preloaded for DS25)					
Fiber Channel/FDDI support	Direct connection to SAN with physical KGPSA or compatible EMULEX HBA adapters / Direct connection to FDDI network with physical DEFFA adapters					
Console/Serial lines	OPA0 console attached to a Windows terminal emulator, a physical serial port (COMxx: device), or a TCP/IP socket					
Supported operating systems	OpenVMS 7.1-2 – OpenVMS 8.4, Tru64 UNIX 4.0F – 5.1B (also known as: Compaq or HP Tru64 UNIX)			OpenVMS 7.2-1H1 – OpenVMS 8.4, Tru64 UNIX 4.0G – 5.1B (also known as: Compaq or HP Tru64 UNIX)		

## Host system requirements

Host operating system	Windows Server 2012 (R2) Standard Edition 64 bit, Windows Server 2008 R2 Standard and Enterprise (SP1) Editions 64 bit (please notice that only R2 revision is supported), Windows 7 Professional, Enterprise and Ultimate (SP1) Editions 64 bit, Windows 8.1 64 bit on top of a physical host or on VMware ESXi 4.1 update 1 or ESXi 5.x
Host CPU/RAM	Amount of host system CPU cores $\geq 2 \times$ (amount of emulated AXP CPU cores); Host RAM $\geq 2$ GB + (amount of emulated AXP RAM)
Recommended Hardware	HP Proliant servers; Intel Haswell CPU family (Xeon E5 v3 or Core i7 v4); frequency at least 3 GHz

## Ordering information

Unlimited license	CHAXP-801IP-WI	CHAXP-802IP-WI /	CHAXP-804IP-WI	CHAXP-808IP-WI	CHAXP-809IP-WI	CHAXP-909IP-WI
Annual license	CHAXP-801IY-WI	CHAXP-802IY-WI	CHAXP-804IY-WI	CHAXP-808IY-WI	CHAXP-809IY-WI	CHAXP-909IY-WI
Annual GOLD Support	CHAXP-801IU-WI	CHAXP-802IU-WI	CHAXP-804IU-WI	CHAXP-808IU-WI	CHAXP-809IU-WI	CHAXP-909IU-WI
Annual PLATINUM Support	CHAXP-801IT-WI	CHAXP-802IT-WI	CHAXP-804IT-WI	CHAXP-808IT-WI	CHAXP-809IT-WI	CHAXP-909IT-WI
Backup license	CHAXP-801IK-WI	CHAXP-802IK-WI	CHAXP-804IK-WI	CHAXP-808IK-WI	CHAXP-809IK-WI	CHAXP-909IK-WI
Additional CPU	CHAXP-CPUIP-WI	CHAXP-CPUIP-WI	CHAXP-CPUIP-WI	CHAXP-CPUIP-WI	CHAXP-CPUIP-WI	CHAXP-CPUIP-WI

«Copyright © 2014 Stromasys Inc. All rights reserved. CHARON name / logo is a trademark of Stromasys SA» - zastratecrea.com

### STROMASYS INC

Americas Region  
2840 Plaza Place,  
Ste 450  
Raleigh, NC 27612  
United States of America  
Phone: +1 919 239 8450  
Fax: +1 919 239 8451  
us.sales@stromasys.com

### STROMASYS SA

Europe, Middle East & Africa  
Avenue Louis-Casali 84  
5<sup>th</sup> Floor  
1216 Cointrin  
Switzerland  
Phone: +41 22 794 1070  
Fax: +41 22 794 1073  
emea.sales@stromasys.com

### STROMASYS ASIA PACIFIC LTD

Asia Pacific Region  
28/F, Room D, Tower B, Billion Centre  
1 Wang Kwong Road  
Kowloon Bay  
Hong Kong  
Phone: +852 2853 1600  
Fax: +852 2853 1699  
apac.sales@stromasys.com



stromasys  
engineered solutions