

Charon-AXP/DS10, /DS20, /ES40, /GS80, /GS160, and /GS320 for Windows

Product version 4.8

Document: 60-15-086-004

DESCRIPTION

Stromasys **Charon-AXP/DS/ES/GS** are members of the Charon-AXP cross-platform hardware virtualization product family. They are designed to replace the following DEC AlphaServer computer systems:

Charon-AXP product	Hardware to replace
Charon-AXP/DS10	AlphaServer DS10, DS15
Charon-AXP/DS20	AlphaServer DS20, DS25
Charon-AXP/ES40	AlphaServer ES40, ES45, ES47
Charon-AXP/GS80	AlphaServer GS80, GS60, ES80
Charon-AXP/GS160	AlphaServer GS140, GS160
Charon-AXP/GS320	AlphaServer GS320, GS1280

Charon-AXP emulates most of the original Alpha-specific hardware. It runs the original Alpha binary code, including the operating systems OpenVMS and Tru64 UNIX, the layered products, and applications, which all continue to work as before. A small number of changes to the original software (operating system, layered products, or applications) may be required. The Tru64 kernel may have to be rebuilt.

NETWORK

Charon-AXP virtualizes the 10/100 Mbps Ethernet controllers of the DEC 21x4x and Intel 825x families, ensuring support of any AlphaServer installation. Any protocol supported on a physical Alpha Ethernet link (DECnet, TCP/IP, and LAT) will work on a virtualized Charon link. The Charon network adapter is recognized by the operating system as a 10/100 Mbps link, but since the adapter is virtualized, it may exceed that speed when connected to a 1 Gbps / 10 Gbps adapter in the host system. The network performance also depends on design limitations of the guest OS (VMS or Tru64).

STORAGE

Charon-AXP provides support for Alpha disk, tape, and CD/DVD storage devices via virtual KZPBA SCSI and KGPSA FC adapters, translating them into any modern technology (SCSI, SATA, SAS) by means of virtual disk images on a Windows filesystem or physical LUNs attached locally or remotely by iSCSI, SAN, or NAS.

PCI PASSTHROUGH

Emulex FC adapters compatible with the original AlphaServer hardware (FC KGPSA), serial line PBXDA adapters, and FDDI DEPFA adapters can be used by Charon-AXP to provide direct access to SAN infrastructure, serial lines, and FDDI networks, equivalent to the physical Alpha access. Using PCI Passthrough enables up to 50% disk I/O performance improvement compared to using virtual storage controllers. It is recommended for high performance configurations with access to SAN infrastructures.

HOST SYSTEM REQUIREMENTS

A physical system or virtual appliance with multi-core CPUs (Intel Xeon v4 E3, E5, and E7 CPUs with a clock frequency of 3GHz and above are recommended), dedicated Ethernet adapters, an optional USB port for the license key, and enough disk space to keep the OpenVMS or Tru64 data. For every emulated AXP CPU, Charon must have exclusive access to at least 2 CPU cores on the host system. For each emulated Alpha system, Charon-AXP requires at least 2 GB of RAM plus the amount of RAM assigned to the emulated Alpha system.

PERFORMANCE

SPEC2000 tests running on Tru64 5.1B on Charon-AXP emulating an AlphaServer ES45 deliver about **SPEC2000 INT 834** and **SPEC2000**

FP 678 per CPU on a system with Intel Core i7-4790K 4GHz CPUs. Charon-AXP benefits from the newer, faster hardware, offering equal or better performance compared to most Alpha systems. The constant improvements Stromasys makes to the Charon products, together with rapidly developing faster hardware, will further shift the balance in favor of cross-platform virtualization.

Full SPEC2000 data for all physical Alpha systems can be accessed online at <https://www.spec.org/cpu2000/>.

SYSTEM MAINTENANCE

Once installed and configured, the Charon system behaves like the original Alpha system and can be treated as an Alpha. Guest OS and applications operating procedures remain the same. The host operating system does not require a network connection and regular patching after the installation. See user's guide for requirements regarding any updates to the host OS.

LICENSE PROTECTION

A valid license should be permanently available to Charon in the form of a local or network attached USB HASP license dongle, or a Software License. The license contains customer specific parameters and allows remote electronic updates. USB dongles enable a rapid switch-over to another host system as the Charon executable itself can be installed on multiple systems for disaster recovery purposes. Flexible licensing options allow combining multiple instances of different Charon products on a single host system.

DISTRIBUTION

Charon Release notes, User manuals and Software Product Descriptions are available for download from the Stromasys Product Documentation and Knowledge Base web pages. Downloading installation kits and patches requires a partner account or credentials provided by Stromasys on an individual basis.

CHARON UTILITIES

Charon-AXP on Windows is delivered with the **Charon Virtual Machines Manager**, a single-window application which consolidates all Charon management tasks: creating and configuring Charon instances, managing Charon licenses, configuring host hardware resources for Charon needs, etc. The following applications are invoked from Charon VM manager:

- **HASP License Details** for viewing Charon licenses
- **License Update Tool** for updating Charon licenses
- **Sentinel Admin Control Center** for license management
- **Network Control Center** for managing Charon network drivers and settings
- **Device Check** for providing configuration assistance for directly connected host devices
- **Virtual Disk Tool** for creating empty disk image files (.vdisk)

The following command line utilities are also available:

- **Virtual Disk Tool** for creating empty disk image files (.vdisk)
- **MTD** for transferring data between physical tapes and Charon tape container files, and for converting virtual tape formats between Charon-AXP variants.

Stromasys **Charon Guest Utilities for OpenVMS** version 6.1 and above are supplied on a disk image to provide the following functionality:

- **Tape Utilities Package** for manipulating virtual tape images and managing a virtual SCSI tape changer
- **VMS bypass driver** for emulating DU/DR/DG/DQ/DI disk devices
- **Power consumption optimization (IDLE) VMS utility** for implementing energy saving mode when a virtual AXP CPU is idle

VIRTUALIZED HARDWARE

Charon product	Charon-AXP/DS10	Charon-AXP/DS20	Charon-AXP/ES40	Charon-AXP/GS80	Charon-AXP/GS160	Charon-AXP/GS320
Emulated AlphaServer model	DS10, DS15	DS20, DS25	ES40, ES45, ES47	GS60, GS80, ES80	GS140, GS160	GS320, GS1280
Alpha CPUs (base / maximum)	1 / 1	1 / 2	2 / 4	4 / 8	8 / 16	16 / 32
Emulated RAM	Up to 32 GB	Up to 32 GB	Up to 32 GB	Up to 64 GB	Up to 128 GB	Up to 256 GB
Available virtual PCI slots	4	6	10	27	27	27
Storage adapter support	Emulated PCI SCSI KZPBA adapters (2 preloaded for DS20, DS25; 1 preloaded for GS series); emulated PCI FC KGPSA adapters; up to 120 storage units (disks, tapes, and CD/DVD) supported simultaneously; emulated Acer Labs 1543C IDE/ATAPI controller (1 preloaded; only virtual IDE CD/DVD devices)					
Disk storage support	Virtual disk images on a local and remote Windows file system (.vdisk container files); physical SCSI disks and partitions; iSCSI disks; SAN attached storage volumes (\\.\PhysicalDriveX devices)					
Tape storage support	Virtual tape images on a local and remote Windows file system (.vtape container files); physical SCSI tape drives (\\.\TapeX or \\.\SCSI devices)					
CDROM / Floppy disk support	Virtual CD/DVDs images (.iso container files); physical CD/DVD drives (\\.\CdRomX devices) / Physical floppy drive 1.44 MB (\\.\A: device)					
Ethernet network support	Emulated PCI DEC 21x4x adapters: DE435, DE450, DE500AA, and DE500BA (2 DEC 21143 controllers preloaded for DS10, DS15; 1 preloaded for DS25); emulated PCI Intel 82558 10/100 Mbps adapters: DE602 and DE602AA					
Fibre Channel / FDDI support	Direct connection to SAN with physical KGPSA or compatible FC EMULEX HBA adapters (up to 8 Gbps) in Passthrough mode; direct connection to SAN with Windows supported FC HBA adapters in Presentation mode / Direct connection to FDDI network with physical DEFFPA adapters					
Console / Serial lines	OPA0 console attached to a Windows terminal emulator, a physical serial port (COMxx: device), or a TCP/IP socket					
Supported operating systems	OpenVMS 7.1-2 – OpenVMS 8.4, Tru64 UNIX 4.0F – 5.1B (also known as Compaq or HP Tru64 UNIX)			OpenVMS 7.2-1H1 – OpenVMS 8.4, Tru64 UNIX 4.0G – 5.1B (also known as Compaq or HP Tru64 UNIX)		

Host system requirements

Host operating system	Microsoft Windows Server (64 bit)		Microsoft Windows (64 bit)			Physical host or Hypervisor	
	2016 and 2012 R2 (Standard, Datacenter)	2008 R2 SP1 (Standard, Enterprise)	7 SP1 (Professional, Ultimate)	8.1 Professional	10 (Professional, Enterprise)	ESXi 5.5 and 6.x up to 6.5	Microsoft Hyper-V
Host CPU/RAM	Number of host system CPU cores $\geq 2 * (\text{number of emulated AXP CPU cores})$; host RAM = (2 GB + AXP RAM) per emulated AXP minimum. These guidelines for host system sizing must be reviewed for every use case.						
Recommended hardware	HP ProLiant G9 servers; Intel Xeon v4 E3, E5 and E7 CPUs; Intel Core 7 th generation CPUs; CPU frequency 3 GHz and above						

Ordering information

Perpetual license	CHAXP-801IP	CHAXP-802IP	CHAXP-804IP	CHAXP-808IP	CHAXP-809IP	CHAXP-909IP
Annual license	CHAXP-801IY	CHAXP-802IY	CHAXP-804IY	CHAXP-808IY	CHAXP-809IY	CHAXP-909IY
Annual GOLD support (9*5)	CHAXP-801IU	CHAXP-802IU	CHAXP-804IU	CHAXP-808IU	CHAXP-809IU	CHAXP-909IU
Annual PLATINUM support (24*7)	CHAXP-801IT	CHAXP-802IT	CHAXP-804IT	CHAXP-808IT	CHAXP-809IT	CHAXP-909IT
Backup license	CHAXP-801IK	CHAXP-802IK	CHAXP-804IK	CHAXP-808IK	CHAXP-809IK	CHAXP-909IK
Additional CPU	N/A	CHAXP-CPUIP	CHAXP-CPUIP	CHAXP-CPUIP	CHAXP-CPUIP	CHAXP-CPUIP

STROMASYS INC

Americas Region
2840 Plaza Place
Ste 450
Raleigh, NC 27612
United States of America
Phone: +1 919 239 8450
Fax: +1 919 239 8451
us.sales@stromasys.com

STROMASYS SA

Europe, Middle East & Africa
Avenue Louis-Casai 84
5th Floor
1216 Cointrin-Geneva
Switzerland
Phone: +41 22 794 1070
Fax: +41 22 794 1073
emea.sales@stromasys.com

STROMASYS ASIA PACIFIC LTD

Asia Pacific Region
Room 1102, 11/F, Lee Garden One
33 Hysan Avenue
Causeway Bay, Hong Kong
Hong Kong SAR of People's Republic of China
Phone: +852 3959 8788
Fax: +852 3959 8800
apac.sales@stromasys.com



stromasys
engineered solutions