



### DESCRIPTION

Charon-SSP is a member of Charon cross-platform hardware virtualization product family that creates a virtual replica of sun4m, sun4u or sun4v SPARC family members on a standard x86-64 computer system running Linux on top of physical hardware, or a Hypervisor. Charon-SSP lets users of end-of-life SPARC servers/stations continue to use their applications without any changes while lowering operational costs and energy consumption. Multiple instances can run on a single x86-64 standard host or existing virtualization infrastructure providing the benefits of consolidation as well as easy management and maintenance of these legacy systems.

Charon-SSP provides the following virtualized SPARC models:

- *Charon-SSP/4M*: based on the SPARC-V8 32-Bit processor specifications, MBUS for processor/memory interconnection and SBUS for IO peripherals.
- *Charon-SSP/4U*: based on the SPARC-V9 64-bit processor specifications, UPA bus for processor/memory interconnection and PCI bus for IO peripherals.
- *Charon-SSP/4U+*: same as /4U, uses Intel VT-x /EPT or AMD-v/NPT to offload SPARC MMU operations to hardware. The host system must run on physical hardware.
- *Charon-SSP/4V*: based on the SPARC-V9 64-bit processor specifications and the sun4v hypervisor architecture. Each emulator instance supports one LDom.
- *Charon-SSP/4V+*: same as /4V, uses Intel VT-x /EPT or AMD-v/NPT to offload SPARC MMU operations to hardware. The host system must run on physical hardware.

### NETWORK

Charon-SSP maps one host physical Ethernet adapter for each emulated NIC. Alternatively, it can bridge a physical Ethernet adapter with a number of tap devices to allow communication between Charon-SSP instances and the Linux host while multiplexing traffic across the physical Ethernet adapter for external communication. All Solaris network protocols are supported transparently as well as Solaris IP multipathing and Solaris VNICs. Network booting and JumpStart installation are supported for Solaris 2.4 to Solaris 10 (non-cloud installations).

### GRAPHIC ENVIRONMENT

Solaris CDE, OpenWindow desktop and Java Desktop graphics environment are supported on Charon-SSP using a nested X11 server running on the host. Native graphics (Charon-SSP/4M/4U (+) only) are implemented via emulated CGTHREE, CGSIX and RageXL framebuffer with resolutions ranging from 800x600 to 1600x1280 pixels. Dual monitor configurations are supported on these framebuffers for larger virtual desktops.

### AUDIO

DBR12 + CS4215 mmcodec virtualized components provide 8-bit/16-bit mono/stereo sound in u-Law, a-Law, linear formats. Remote audio supported on Linux / PulseAudio server. Available on Charon-SSP/4M/4U (+) only.

### STORAGE

Charon-SSP provides virtualization for SCSI controllers and peripherals as follows:

- Virtual disks and tapes as container files residing on host file systems
- Raw partitions
- Physical disks / tapes.
- iSCSI targets

In addition, Charon-SSP/4V supports VDS virtual and physical disk and CD-ROM devices, Charon-SSP/4M supports floppy disks.

### POWER SAVING

Charon-SSP provides a feature to reduce CPU power consumption on the Linux host when the Solaris OS is idle. This feature can be enabled using the following options:

- *Balanced*: uses processor power saving instructions to disable pipeline and reduce energy consumption.
- *Power save*: this option uses CPU thread suspension on Solaris IDLE condition to reduce host CPU usage.

### MANAGEMENT

Charon Manager for Charon-SSP is a graphical user interface for creating, configuring, starting and stopping instances of virtual SPARC systems. It also provides access to the virtual consoles and log files as well as, for example, the following tools:

- Create Virtual Disk/Tape/Floppy
- License viewing and updating
- Host information
- Virtual network creation and deletion
- X11 server configuration, starting and stopping
- Console configuration

## PERFORMANCE

Charon-SSP supports a 2-level dynamic instruction translation engine (Client JIT and Server JIT) for Charon-SSP/4U and /4V. Charon-SSP/4V(+) delivers the same level of performance as /4U(+). The table shows a virtual SPARC CPU test run under Solaris 10 on Charon-SSP/4U/4V(+) with Server JIT configuration, on a HP Proliant DL380 Gen 10 @3.0GHz Intel CPU.

|                |     | SSP/4U | SSP/4U+ | SSP/4V | SSP/4V+ |
|----------------|-----|--------|---------|--------|---------|
| <b>CPU2000</b> | INT | 1012   | 1491    |        |         |
|                | FP  | 1238   | 1951    |        |         |
| <b>CPU2006</b> | INT |        |         | 191    | 265     |
|                | FP  |        |         | 160    | 217     |



## DISTRIBUTION

Charon-SSP is distributed as:

- Baremetal: installation ISO image that contains host operating system, Charon-SSP, additional packages, and the Baremetal GUI.
- RPM packages: Charon-SSP packages for Oracle Linux, Red Hat, and CentOS are available upon request.
- Cloud-specific images containing a customized Linux version and the Charon-SSP software (at time of writing AWS, OCI, Azure, GCP). Depending on the cloud platform, the images can be Automatic Licensing (AL) images (Stromasys-operated license server) or Virtual Environment (VE) images (customer-operated Virtual Environment License Server). The VE license functionality is also available on IBM cloud and VMware via conventional RPM package installation.

## VIRTUALIZED HARDWARE AND GUEST OPERATING SYSTEMS

|   | Charon-SSP/4M (32 bit)                        | Charon-SSP/4U(+) <sup>3)</sup> (64 bit) | Charon-SSP/4V(+) <sup>3)</sup> (64-bit)  |
|---|---|---|--|
| <b>Number of SPARC CPUs (Type, Min/Max)</b>         | SPARC V8 1/4                                  | SPARC V9 1/24                           | SPARC V9 1/64                            |
| <b>Emulated RAM</b>                                 | 64MB to 512MB                                 | 1GB to 128GB                            | 1GB to 1024GB                            |
| <b>Bus type: Slots</b>                              | SBUS: 12 slots                                | PCI: 16 slots                           | PCI (slots n/a)                          |
| <b>SCSI controllers</b>                             | 1   | 2                                       | 2  |
| <b>Max. number of SCSI target IDs <sup>4)</sup></b> | 7   | 30                                      | 30                                       |
| <b>Disks supported</b>                              | physical/partition/vdisk                      | physical/partition/vdisk                | physical/partition/vdisk                 |
| <b>CD/DVD support <sup>1)</sup></b>                 | physical/ISO image                            | physical/ISO image                      | physical/ISO image                       |
| <b>Tape support <sup>1)</sup></b>                   | physical/vtape                                | physical/vtape                          | physical/vtape                           |
| <b>Ethernet controllers</b>                         | 2   | 19                                      | 4  |
| <b>Serial ports <sup>1)</sup></b>                   | 10  | 34                                      | 17 (incl. vconsole)                      |
| <b>Graphics support</b>                             | CGTHREE, CGSIX, X11 nested server             | RAGE XL, CGSIX, X11 nested server       | —  |
| <b>VDS storage devices</b>                          | —   | —                                       | 120 <sup>1)</sup>                        |
| <b>Audio</b>  | DBRIe+CS4215 codec                            | DBRIe+CS4215 codec                      | —  |
| <b>PCI pass-through <sup>1)</sup></b>               | —   | NI IEEE488 GPIB<br>Digi Serial Adapter  | —  |
| <b>USB ports <sup>1)</sup></b>                      | —   | 1                                       | 1  |
| <b>Floppy drive <sup>1)</sup></b>                   | 1   | —                                       | —  |
| <b>Parallel ports <sup>1)</sup></b>                 | 1   | —                                       | —  |
| <b>Guest OS support</b>                             | SunOS 4.1.3/4.1.4<br>Solaris 2.3 to Solaris 9 | Solaris 2.5.1 to Solaris 10             | Solaris 10 to Solaris 11.4 <sup>2)</sup> |

<sup>1)</sup> **Restrictions for cloud environments:** no physical CD-ROM, physical tape, PCI pass-through, floppy, parallel port, or USB support; only 2 built-in serial ports.

<sup>2)</sup> Please refer to the Charon-SSP user's guide for more detail.

<sup>3)</sup> Charon-SSP/4U+/4V+ are only supported on physical hardware running a Linux kernel supported by Stromasys, e.g., on Charon-SSP Baremetal or certain cloud-specific images (depending on hardware options offered by cloud provider). Please refer to the Charon-SSP user's guide for more detail.

<sup>4)</sup> The numbers show the max. number of SCSI target IDs. Each SCSI target ID can have up to 8 LUNs. Therefore, the overall number of SCSI devices can be larger than the number of target IDs. The exact number depends on the emulated hardware, the guest operating system version, and the SCSI devices used.

## HOST REQUIREMENTS

| Host characteristic          | Description   |
|------------------------------|---|
| <b>Operating system</b>      | Version 7.x, 8.1, and 8.2 of Oracle Linux, RHEL and CentOS (all 64-bit)<br>(Charon-SSP Baremetal and cloud-specific images include the required host operating system). |
| <b>Number of host cores</b>  | At least 2 (3 for Server JIT) + number of emulated processors per virtual SPARC VM. <sup>1)</sup>   |
| <b>Memory size</b>           | At least 6GB (10GB for Server JIT) + amount of emulated memory per virtual SPARC VM. <sup>1)</sup>  |
| <b>Recommended hardware</b>  | Intel Server based on Haswell v3 processors or later, or Desktop Core I7 (CPU frequency at least 3.0GHz). AMD processors of the same or higher performance.             |
| <b>Supported hypervisors</b> | VMware ESXi 6.5 and above, Xen, Microsoft Hyper-V, Linux KVM; (hypervisors not supported for Charon-SSP/4U+/4V+) <sup>2)</sup>  |

<sup>1)</sup> Minimum requirements. Please refer to the Charon-SSP user's guide for more detail, and contact your Stromasys representative for workload-dependent sizing guidance.  
<sup>2)</sup> Hyper-V: local HASP license dongles not supported.

## CHARON-SSP PRODUCTS AND PART NUMBERS

This section is not applicable to cloud-specific Charon-SSP AL images. They are licensed automatically based on the selected shape / instance type.

| Charon-SSP product       | Emulated CPU type    | CPU / RAM limitations | GOLD annual subscription <sup>2)</sup> | PLATINUM annual subscription <sup>2)</sup> | Evaluation license <sup>2)</sup> | Backup / Spare license <sup>2)</sup> |
|--------------------------|----------------------|-----------------------|--|--|----------------------------------|--------------------------------------|
| <b>Charon-SSP/4M</b>     | V8                   | 4 / 512MB             | CHSSP-4M-ICG                           | CHSSP-4M-ICP                               | CHSSP-4M-IV                      | CHSSP-4M-IK / CHSSP-4M-IS            |
| <b>Charon-SSP/4U LL</b>  | V9                   | 1 / 1GB               | CHSSP-4ULL-ICG                         | CHSSP-4ULL-ICP                             | CHSSP- 4ULL-IV                   | CHSSP- 4ULL-IK / CHSSP- 4ULL-IS      |
| <b>Charon-SSP/4U ML</b>  | V9                   | 12 / 64GB             | CHSSP-4UML-ICG                         | CHSSP-4UML-ICP                             | CHSSP- 4UML-IV                   | CHSSP- 4UML-IK / CHSSP- 4UML-IS      |
| <b>Charon-SSP/4U HL</b>  | V9                   | 24 / 128GB            | CHSSP-4UHL-ICG                         | CHSSP-4UHL-ICP                             | CHSSP- 4UHL-IV                   | CHSSP- 4UHL-IK / CHSSP- 4UHL-IS      |
| <b>Charon-SSP/4U+ LL</b> | V9 (+) <sup>1)</sup> | 1 / 1GB               | CHSSP-4U+LL-ICG                        | CHSSP-4U+LL-ICP                            | CHSSP- 4U+LL-IV                  | CHSSP- 4U+LL-IK / CHSSP- 4U+LL-IS    |
| <b>Charon-SSP/4U+ ML</b> | V9 (+) <sup>1)</sup> | 12 / 64GB             | CHSSP-4U+ML-ICG                        | CHSSP-4U+ML-ICP                            | CHSSP- 4U+ML-IV                  | CHSSP- 4U+ML-IK / CHSSP- 4U+ML-IS    |
| <b>Charon-SSP/4U+ HL</b> | V9 (+) <sup>1)</sup> | 24 / 128GB            | CHSSP-4U+HL-ICG                        | CHSSP-4U+HL-ICP                            | CHSSP- 4U+HL-IV                  | CHSSP- 4U+HL-IK / CHSSP- 4U+HL-IS    |
| <b>Charon-SSP/4V LL</b>  | V9                   | 4 / 128GB             | CHSSP-4VLL-ICG                         | CHSSP-4VLL-ICP                             | CHSSP-4VLL-IV                    | CHSSP- 4VLL-IK / CHSSP- 4VLL-IS      |
| <b>Charon-SSP/4V ML</b>  | V9                   | 32 / 1TB              | CHSSP-4VML-ICG                         | CHSSP-4VML-ICP                             | CHSSP-4VML-IV                    | CHSSP- 4VML-IK / CHSSP- 4VML-IS      |
| <b>Charon-SSP/4V HL</b>  | V9                   | 64 / 1TB              | CHSSP-4VHL-ICG                         | CHSSP-4VHL-ICP                             | CHSSP-4VHL-IV                    | CHSSP- 4VHL-IK / CHSSP- 4VHL-IS      |
| <b>Charon-SSP/4V+ LL</b> | V9 (+) <sup>1)</sup> | 4 / 128GB             | CHSSP-4V+LL-ICG                        | CHSSP-4V+LL-ICP                            | CHSSP-4V+LL-IV                   | CHSSP- 4V+LL-IK / CHSSP- 4V+LL-IS    |
| <b>Charon-SSP/4V+ ML</b> | V9 (+) <sup>1)</sup> | 32 / 1TB              | CHSSP-4V+ML-ICG                        | CHSSP-4V+ML-ICP                            | CHSSP-4V+ML-IV                   | CHSSP- 4V+ML-IK / CHSSP- 4V+ML-IS    |
| <b>Charon-SSP/4V+ HL</b> | V9 (+) <sup>1)</sup> | 64 / 1TB              | CHSSP-4V+HL-ICG                        | CHSSP-4V+HL-ICP                            | CHSSP-4V+HL-IV                   | CHSSP- 4V+HL-IK / CHSSP- 4V+HL-IS    |

<sup>1)</sup> Accelerated by offloading part of the emulated CPU workload onto hosting hardware  
<sup>2)</sup> Please contact the Stromasys Sales team for Charon licensing details  
<sup>3)</sup> Please refer to Charon Service Descriptions for GOLD and PLATINUM terms, conditions, and SLAs

