

Charon-VAX/66x0 PLUS for Windows

Product version 4.8

Document: 30-15-080-003



DESCRIPTION

Stromasys **Charon-VAX/6610 PLUS, Charon-VAX/6620 PLUS, Charon-VAX/6630 PLUS, and Charon-VAX/6660 PLUS** are members of the Charon-VAX cross-platform hardware virtualization product family. They are designed to replace **XMI based VAX 6000, 7000, 8000, and 10000 series** systems by their virtual equivalents running on an x86-64 compatible standard computer system. Charon-VAX creates a virtual replica of the original DEC VAX hardware, allowing the VAX/VMS operating system and all software running in that environment to continue to work as before in their existing, binary form. No or only minimal configuration changes to the original software (operating system, layered products, and applications), operational procedures, and management are required.

VAX hardware	Virtual VAX 66x0 product
VAX 6610, VAX 7610	⇒ Charon-VAX/6610 PLUS
VAX 6620, VAX 7620	⇒ Charon-VAX/6620 PLUS
VAX 6630, VAX 7630	⇒ Charon-VAX/6630 PLUS
VAX 6660, VAX 7660	⇒ Charon-VAX/6660 PLUS

NETWORK

Charon-VAX virtualizes the Ethernet controllers present in the original VAX hardware. Any protocol supported on these controllers (DECnet, TCP/IP, LAT) will work on the virtualized link.

STORAGE

Charon-VAX/66x0 PLUS provides support for the following VAX storage device types: XMI, BI, (T)MSCP, CI, and DSSI. Charon translates the VAX storage to any modern technology (SCSI, SATA, SAS) by means of virtual disk images on a Windows filesystem or physical LUNs attached locally or remotely by iSCSI, SAN, or NAS.

HOST SYSTEM REQUIREMENTS

A physical system or virtual appliance with a multi-core CPU (Intel Xeon v4 E3, E5, and E7 CPUs with a clock frequency of 3GHz and above are recommended; the number of available CPU cores should be greater or equal to number of emulated VAX CPUs plus 2), dedicated Ethernet adapters, an optional USB port for the license key and enough disk space to keep the VAX/VMS data. Charon-VAX/66x0 requires up to 6 GB host RAM (refer to page 2 for details).

OPERATING SYSTEM REQUIREMENTS

Microsoft Windows Server (64 bit)			Physical host or Hypervisor	
2016 and 2012 R2 (Standard, Datacenter)	2008 R2 SP1 (Standard, Enterprise)		ESXi 5.5 and 6.x up to 6.5	Microsoft Hyper-V
Microsoft Windows (32 bit and 64 bit)				
7 SP1 (Professional, Ultimate)	8.1 Professional	10 (Professional, Enterprise)		

LICENSE PROTECTION

A valid license should be permanently available to Charon in the form of a local or network attached USB HASP license dongle, or a Software License. The license contains customer specific parameters and allows remote electronic updates. USB dongles enable a rapid switch-over to another host system as the Charon executable itself can be installed on multiple systems for disaster recovery purposes. Flexible licensing options allow combining multiple instances of different Charon products on a single host system.

SYSTEM MAINTENANCE

Once installed and configured, the Charon system behaves like the original VAX system, and can be treated as a VAX. Guest OS and applications operating procedures remain the same. The host operating system does not require a network connection and regular patching after the installation. See user's guide for requirements regarding any updates to the host OS.

PERFORMANCE

	Hardware VAX	Charon-VAX*
VAX 6610	32 VUPS	150 VUPS
VAX 6620	50 VUPS	275 VUPS
VAX 6630	75 VUPS	400 VUPS
VAX 6660	150 VUPS	800 VUPS

*: On a system based on Intel Core 7th generation 3.2 GHz CPUs

DISTRIBUTION

Charon Release notes, User manuals and Software Product Descriptions are available for download from the Stromasys Product Documentation and Knowledge Base web pages. Downloading installation kits and patches requires a partner account or credentials provided by Stromasys on an individual basis.

CHARON UTILITIES

Charon-VAX on Windows is delivered with the **Charon Virtual Machines Manager**, a single-window application which consolidates all Charon management tasks: creating and configuring Charon instances, managing Charon licenses, configuring host hardware resources for Charon needs, etc. The following applications are invoked from Charon VM manager:

- **HASP License Details** for viewing Charon licenses
- **License Update Tool** for updating Charon licenses
- **Sentinel Admin Control Center** for license management
- **Network Control Center** for managing Charon network drivers and settings
- **Device Check** for providing configuration assistance for directly connected host devices
- **Virtual Disk Tool** for creating empty disk image files (.vdisk)

The following command line utilities are also available:

- **Virtual Disk Tool** for creating empty disk image files (.vdisk)
- **MTD** for transferring data between physical tapes and Charon tape container files
- **HOSTprint** for redirecting an emulated QBUS LPV11 device (parallel port) output to a Windows local or network printer

Stromasys **Charon Guest Utilities for OpenVMS** version 6.1 and above are supplied on a disk image to provide the following functionality:

- **Tape Utilities Package** for manipulating virtual tape images and managing a virtual SCSI tape changer
- **Power consumption optimization (IDLE) VMS utility** for implementing energy saving mode when a virtual VAX CPU is idle
- **Slowdown VMS utility**: for slowing down Charon virtual CPU to match hardware VAX performance level
- **Shutdown VMS utility** for an orderly shutdown (Charon after VMS)



VIRTUALIZED HARDWARE

	Charon-VAX/6610 PLUS	Charon-VAX/6620 PLUS	Charon-VAX/6630 PLUS	Charon-VAX/6660 PLUS
Virtualized VAX model	VAX6000-610	VAX6000-620	VAX6000-630	VAX6000-660
Virtualized VAX CPU	KA66-A 1 VAX CPU	KA66-A 2 VAX CPUs	KA66-A 3 VAX CPUs	KA66-A 4, 5, or 6 VAX CPU's
Earliest VMS version	5.5-2			
Max. virtual VAX memory	1 GB	2 GB	2 GB on 32-bit Windows 3 GB on 64-bit Windows	2 GB on 32-bit Windows 3 GB on 64-bit Windows
Internal bus	XMI; BI through virtual XMI to BI controller			
SCSI and QBUS buses	N/A			
Emulated VAX disks	Virtual disk images (container files) and physical SCSI disks and partitions on KDM70 XMI disk/tape controllers; CIXCD CI disk controllers; HSJ50 storage controllers			
Emulated VAX tapes	KDM70 XMI disk/tape controller with container files (boot from tape is not supported)			
Ethernet	Multiple emulated DEMNA Ethernet adapters up to the available maximum slots on the emulated XMI bus. Connection speed on the emulated VAX level is 10, 100 Mbps, and 1Gbps ¹⁾			
VAX/VMS clustering	NI clusters; Shared Disk Clusters with emulated CIXCD and HSJ50 controllers			
Host memory requirement	3 GB	4 GB	6 GB	6 GB

¹⁾ The effective aggregate throughput depends on the host system performance

Each virtual VAX model follows the characteristics of its VAX hardware equivalent. It requires the corresponding level of license units and supports the peripherals particular to that VAX model. The virtual VAX does not include diagnostic and maintenance modes or delays to simulate mechanical device behavior

Ordering information	Charon-VAX/6610 PLUS	Charon-VAX/6620 PLUS	Charon-VAX/6630 PLUS	Charon-VAX/6660 PLUS
Perpetual runtime license	CHVX-261-PG	CHVX-262-PH	CHVX-263-PH	CHVX-260-PH
One year license	CHVX-261-YG	CHVX-262-YH	CHVX-263-YH	CHVX-260-YH
Backup license (720 hours)	CHVX-261-KG	CHVX-262-KH	CHVX-263-KH	CHVX-260-KH
Annual GOLD support (9*5)	CHVX-261-UG	CHVX-262-UH	CHVX-263-UH	CHVX-260-UH
Annual PLATINUM support (24*7)	CHVX-261-TG	CHVX-262-TH	CHVX-263-TH	CHVX-260-TH

STROMASYS INC

Americas Region
2840 Plaza Place
Ste 450
Raleigh, NC 27612
United States of America
Phone: +1 919 239 8450
Fax: +1 919 239 8451
us.sales@stromasys.com

STROMASYS SA

Europe, Middle East & Africa
Avenue Louis-Casai 84
5th Floor
1216 Cointrin-Geneva
Switzerland
Phone: +41 22 794 1070
Fax: +41 22 794 1073
emea.sales@stromasys.com

STROMASYS ASIA PACIFIC LTD

Asia Pacific Region
Room 1102, 11/F, Lee Garden One
33 Hysan Avenue
Causeway Bay, Hong Kong
Hong Kong SAR of People's Republic of China
Phone: +852 3959 8788
Fax: +852 3959 8800
apac.sales@stromasys.com



stromasys
engineered solutions