

## Charon-VAX/XK PLUS, /XL, and /XL PLUS for Windows

Product version 4.8

Document: 30-15-079-003



### DESCRIPTION

Stromasys **Charon-VAX/XK PLUS, Charon-VAX/XL, and Charon-VAX/XL PLUS** are members of the Charon-VAX cross-platform hardware virtualization product family. They are designed to replace **VAXserver, VAXstation, and MicroVAX models 3600 and 3900; VAX 3100-98; VAX 4000-108; VAX 4000-700 and 4000-705; and VAX 6000-310** systems by their virtual equivalents running on an x86-64 compatible standard computer system. Charon-VAX creates a virtual replica of the original DEC VAX hardware, allowing the VAX/VMS operating system and all software running in that environment to continue to work as before in their existing, binary form. No or only minimal configuration changes to the original software (operating system, layered products, and applications), operational procedures, and management are required.

### NETWORK

Charon-VAX virtualizes the Ethernet controllers present in the original VAX hardware. Any protocol supported on these controllers (DECnet, TCP/IP, LAT) will work on the virtualized network link.

### STORAGE

Charon-VAX/XK/XL (PLUS) provides support for the following VAX storage device types: (T)MSCP, DSSI and SCSI. Charon translates the VAX storage to any modern technology (SCSI, SATA, SAS) by means of virtual disk images on a Windows filesystem or physical LUNs attached locally or remotely by iSCSI, SAN, or NAS.

### HOST SYSTEM REQUIREMENTS

A physical system or virtual appliance with a dual-core CPU (Intel Xeon v4 E3, E5, and E7 CPUs with a clock frequency of 3GHz and above are recommended), dedicated Ethernet adapters, an optional USB port for the license key and enough disk space to keep the VAX/VMS data. Charon-VAX/XL requires a minimum of 2 GB host memory; Charon-VAX/XK PLUS and /XL PLUS require 3 GB.

The Charon-VAX device drivers for an external PCI to QBUS adapter, an FPGA Cesium board, and some serial interfaces require Windows 7 32 bit and cannot be used on other versions. Those devices also cannot be used if the host system runs on hypervisors like VMware.

### OPERATING SYSTEM REQUIREMENTS

Microsoft Windows Server (64 bit)		Physical host or Hypervisor
2016 and 2012 R2 (Standard, Datacenter)	2008 R2 SP1 (Standard, Enterprise)	
Microsoft Windows (32 bit and 64 bit)		ESXi 5.5 and 6.x up to 6.5
7 SP1 (Professional, Ultimate)	8.1 Professional 10 (Professional, Enterprise)	

### PERFORMANCE

Charon-VAX is available in a standard and a PLUS version. The PLUS version includes Advanced CPU Emulation (ACE) providing 4 – 6 times better CPU performance compared to the Standard product. On a system based on Intel Core 7<sup>th</sup> generation (3.0 GHz) CPUs, the PLUS version virtual CPU delivers approximately 125 VUPS, the standard version provides about a quarter of this number. For the reference: the original hardware VAX CPU provided from 1 VUP (MicroVAX II) up to 38 VUPS (VAX3100-96). Therefore the VAX virtualization will deliver a major performance improvement.

### CHARON APPLICATION PROGRAM INTERFACE (CHAPI)

CHAPI is an open API to the emulated QBUS bus, thus available for QBUS based emulators. It allows the creation of emulated QBUS devices and connects emulated peripherals, which are implemented by external C++ modules, to the emulator kernel. CHAPI library functions provide standard device elements like registers, interrupt logic, etc.

### SYSTEM MAINTENANCE

Once installed and configured, the Charon system behaves like the original VAX system, and can be treated as a VAX. Guest OS and applications operating procedures remain the same. The host operating system does not require a network connection and regular patching after the installation. See user's guide for requirements regarding any updates to the host OS.

### LICENSE PROTECTION

A valid license should be permanently available to Charon in the form of a local or network attached USB HASP license dongle, or a Software License. The license contains customer specific parameters and allows remote electronic updates. USB dongles enable a rapid switch-over to another host system as the Charon executable itself can be installed on multiple systems for disaster recovery purposes. Flexible licensing options allow combining multiple instances of different Charon products on a single host system.

### DISTRIBUTION

Charon Release notes, User manuals and Software Product Descriptions are available for download from the Stromasys Product Documentation and Knowledge Base web pages. Downloading installation kits and patches requires a partner account or credentials provided by Stromasys on an individual basis.

### CHARON UTILITIES

Charon-VAX on Windows is delivered with the **Charon Virtual Machines Manager**, a single-window application which consolidates all Charon management tasks: creating and configuring Charon instances, managing Charon licenses, configuring host hardware resources for Charon needs, etc. The following applications are invoked from Charon VM manager:

- **HASP License Details** for viewing Charon licenses
- **License Update Tool** for updating Charon licenses
- **Sentinel Admin Control Center** for license management
- **Network Control Center** for managing Charon network drivers and settings
- **Device Check** for providing configuration assistance for directly connected host devices
- **Virtual Disk Tool** for creating empty disk image files (.vdisk)

The following command line utilities are also available:

- **Virtual Disk Tool** for creating empty disk image files (.vdisk)
- **MTD** for transferring data between physical tapes and Charon tape container files
- **HOSTprint** for redirecting an emulated QBUS LPV11 device (parallel port) output to a Windows local or network printer

Stromasys **Charon Guest Utilities for OpenVMS** version 6.1 and above are supplied on a disk image to provide the following functionality:

- **Tape Utilities Package** for manipulating virtual tape images and managing a virtual SCSI tape changer
- **Power consumption optimization (IDLE) VMS utility** for implementing energy saving mode when a virtual VAX CPU is idle
- **Slowdown VMS utility** for slowing down Charon virtual CPU to match hardware VAX performance level
- **Shutdown VMS utility** for an orderly shutdown (Charon after VMS)



## VIRTUALIZED HARDWARE

	VAX 4000-108	VAX 3100-98	MicroVAX, VAXserver, VAXstation 3600/3900	VAX 4700/4705	VAX 6310
<b>Virtualized VAX CPU</b>	KA54-A	KA56-A	KA650-A/B / KA655-A/B	KA692-A/KA694-A	KA-62B
<b>Earliest VMS version</b>	5.5-2 (5.5-2H4 if second SCSI adapter is used)		4.5	5.5-2	5.5-2
<b>Max. virtual VAX memory</b>	XK PLUS: 256 MB; XL and XL PLUS: 512 MB				
<b>XMI and BI subsystems</b>	No			No	Yes (KDB50)
<b>QBUS subsystem</b>	Yes <sup>1) 3)</sup>	No	Yes <sup>1) 3)</sup>	Yes <sup>1) 3)</sup>	No
<b>UNIBUS subsystem</b>	No			No	Yes (TUK50)
<b>DSSI subsystem</b>	Yes (HSD50)	No	No	YES (two built-in PAA/PAB and two optional PAC/PAD DSSI adapters, HSD50 storage controller)	No
<b>SCSI subsystem</b>	2 controllers, each supports 7 SCSI IDs. Each SCSI ID could be used with up to 8 LUNs		No	No	No
<b>Emulated VAX disks</b>	Container files; local, iSCSI and SAN partitions; physical SCSI disks		Container files; local, iSCSI and SAN partitions	Container files; local disk drives, iSCSI and SAN partitions	Container files; local, iSCSI and SAN partitions
<b>Emulated VAX tapes</b>	Container files, Windows tape drives, physical SCSI tape drives				
<b>Network</b>	Up to 5 Ethernet controllers in total including a built-in SGEC and QBUS controllers: DEQNA, DELQA, DESQA	1 built-in Ethernet controller SGEC	Up to 4 QBUS Ethernet controllers: DEQNA, DELQA, DESQA	Up to 5 Ethernet controllers in total including a built-in SGEC and QBUS controllers: DEQNA, DELQA, DESQA	Multiple BI DEBNI Ethernet controllers (limited by number of available virtual bus slots)
<b>Network performance</b>	Standard version supports 10 Mbps connections; PLUS version supports 100 Mbps connections. PLUS version could be used with 1 Gbps connections provided it is tested in advance.				
<b>VAX/VMS clustering</b>	NI or Shared Disk Cluster with emulated MSCP or DSSI controllers	NI Cluster	NI cluster or Shared Disk Cluster with emulated MSCP controllers	NI or Shared Disk Cluster with emulated MSCP or DSSI controllers	NI Cluster
<b>Asynchronous serial lines</b>	QUART (4 lines), CXA16, CXB16, CXY08, DHQ11, DHV11, DHW42-AA, -BA, -CA	QUART (4 lines), DHW42-AA, -BA, -CA	UART, CXA16, CXB16, CXY08, DHQ11, DHV11	CXA16, CXB16, CXY08, DHQ11, DHV11	UART
<b>Graphics subsystem</b>	No	No	Dummy VCB_02 can be loaded in order to force VMS to accept D type licenses <sup>2)</sup>	No	No

<sup>1)</sup> Configurable QBUS components are the MSCP disk controller RQDX3, the TMSCP tape controller TQK50, the serial line controllers as above and the Ethernet controllers DEQNA, DELQA and DESQA. MSCP disk emulation is the preferred storage device emulation in case of heavy disk I/O.

<sup>2)</sup> An X-Windows emulator on a MS Windows or a Linux system can be used to display graphics provided by an X Client running on Charon.

<sup>3)</sup> A 3<sup>rd</sup> party PCI to QBUS adapter can be ordered to connect a physical QBUS basket to Charon-VAX.

**Each virtual VAX model follows the characteristics of its VAX hardware equivalent. It requires the corresponding level of license units and supports the peripherals particular to that VAX model. The virtual VAX does not include diagnostic and maintenance modes or delays to simulate mechanical device behavior.**

Ordering information	Charon-VAX/XK PLUS	Charon-VAX/XL	Charon-VAX/XL PLUS
Perpetual runtime license	CHVX-221-PE	CHVX-021-PF	CHVX-221-PF
One year license	CHVX-221-YE	CHVX-021-YF	CHVX-221-YF
720 hour backup license	CHVX-221-KE	CHVX-021-KF	CHVX-221-KF
Annual GOLD support (9*5)	CHVX-221-UE	CHVX-021-UF	CHVX-221-UF
Annual PLATINUM support (24*7)	CHVX-221-TE	CHVX-021-TF	CHVX-221-TF

### STROMASYS INC

Americas Region  
2840 Plaza Place  
Ste 450  
Raleigh, NC 27612  
United States of America  
Phone: +1 919 239 8450  
Fax: +1 919 239 8451  
us.sales@stromasys.com

### STROMASYS SA

Europe, Middle East & Africa  
Avenue Louis-Casali 84  
5<sup>th</sup> Floor  
1216 Cointrin-Geneva  
Switzerland  
Phone: +41 22 794 1070  
Fax: +41 22 794 1073  
emea.sales@stromasys.com

### STROMASYS ASIA PACIFIC LTD

Asia Pacific Region  
Room 1102, 11/F, Lee Garden One  
33 Hysan Avenue  
Causeway Bay, Hong Kong  
Hong Kong SAR of People's Republic of China  
Phone: +852 3959 8788  
Fax: +852 3959 8800  
apac.sales@stromasys.com



**stromasys**  
engineered solutions